Full Rise Scissor Lift

Model: ME - FSL E35 3.5 Ton



>> Electro Hydraulic <<

Salient Features

- Flush-Mount Scissors lift, no more worries about lowered vehicles or expensive spoilers
- Occupies smaller area
- Electro, Hydraulic & Pneumatic systems
- Pneumatic safeguarded
- Lifting power is higher due to double cylinder structure
- Easy for tyre of mount and dismount and chassis maintenance
- This installation is very tidy and ideal for "Hi-Tech" workshops

Technical Specification

| Lifting capacity | 3.5 Ton |
|--------------------|------------------------|
| Max lifting height | 2050 mm |
| Min lifting height | 330 mm |
| Platform length | 1450 mm - 1750 mm |
| Platform width | 550 mm |
| Lifting speed | <55 seconds |
| Dropping speed | <55 seconds |
| Input air pressure | 6-8 Kg/cm ² |
| Power supply | 380V, 3 Phase, 50Hz |
| Power | 2.2 KW |

Low Rise Scissor Lift

Model: ME - LSL 2.7 Ton



>> Electro Hydraulic <<

Salient Features

- Ideal choice for tyre service, Portable, easy to move.
- Electro hydraulic power system.
- Dual cylinders structure, ensures stable raising and lowering.
- Truck adapters included.
- Four rotated holder can support load safely at any position.

Technical Specification

| Lifting capacity | 2.7 Ton |
|---------------------|-----------------------------|
| Max. lifting height | 1000 mm (adjustable) |
| Min. height | 164 mm |
| Lifting time | 45 seconds |
| Power supply | 230V AC, Single Phase, 50Hz |
| Power | 3.0 HP |

16 www.manatec.in