

Brake Liner Riveting Machine

Model : **ME - BLR 6T**



Salient Features

- Operates by compressed air as power source (air pressure is adjustable)
- Used for riveting and punching rivets of all kinds of brake shoes \ brake disc \ brake drum \ brake lining \ brake pad

Technical Specification

Max riveting force	60KN (6T)
Working air pressure	0-0.8MPa (Adjustable)
Used for rivet diameter	3mm-10mm (Copper, Aluminum & Steel)
Traveler	0-35mm (Adjustable)
Riveter	6 Pcs
Puncher	2 Pcs

Fuel Injector Cleaner & Tester

Model : **ME - FICT**



Salient Features

- Auto clean
- Auto pulse flow test
- Auto drain
- Auto leak test
- R.P.M. test (500-9000)
- Open flow test
- Injector coil test
- Emergency stop switch for safety
- High precision solenoid valve for accuracy
- Pressure regulator adjustable
- Hold option for leak test
- Digital display for AC voltage

Spark Plug Cleaner & Tester

Model : **ME - SPCT**



Salient Features

- Separate plug cleaning chamber consisting of an abrasive system
- Double acting valve for blasting and subsequent cleaning to remove the abrasive and dust
- Different rubber adapters provided for cleaning plugs of 10 mm, 12 mm, 14 mm and 18 mm sizes
- Twin testing chamber connected to the compressed air system for charging the chamber with the necessary control device
- Pressure Regulator is provided for reducing any excess air and releasing pressure in the chamber